


DIMENSIONS: TX / TRX

	TX 7800	TRX 7800
A	708	708
B	1495	1495
C	1190	1190
D	3393	3393
E*	1775÷1875	1775÷1875
F	2272÷2371	2272÷2371
G	2132÷2227	2132÷2227
H	2032÷2127	2032÷2127



*Height calculated with the operator of average height sitting (cm 175)

TECHNICAL DATA: TX / TRX



TX 7800"S" / TRX 7800"S"

Chassis	"ACTIO™" – Full chassis with oscillation • Steering wheels • 4 equal wheel drive • Front and rear final drive TX model > single-direction / TRX model > with Rev-Guide System RGS™									
Engine Type	Diesel direct injection with counter rotating weight system									
	Emissions Regulations: Stage 3A					N° Cylinders: 4 - 16 Valves				
	Displacement (CC): 3319					Power kW/HP (97/68/CE): 52/71				
	Maximum engine revs: 2500					Torque max (Nm/revs): 236/1600				
	Cooling: Water					Tank Capacity (litres): 60 (with roll bar) / 50 (with frame and cab)				
Transmission	Synchronised 32 speed gear box: 16 forward and 16 reverse with synchronised inverter									
PTO	Rear, independent and synchronised at 540/540E rpm with progressive electrohydraulic engagement									
Shaft	Profile 1" 3/8 with 6 splines with facilitated engagement									
Transmission clutch	Mechanic control									
Drive disengagement	Electrohydraulic control on the front									
Rear hydraulic lift	With 3 point hitch cat. 1 - Capacity (Kg): 2150									
Operating Pressure (bar)	140									
Steering	Hydraulic with 2 pistons									
Brakes	Standard: hydraulic front and rear disk brakes in oil bath, rear steering brakes Independent emergency and parking brake: band type on transmission									
Platform	Suspended on Silent Block									
Tyres	250/80-18	300/80-15.3	320/65 R18	300/70 R20	280/70 R18	320/70 R20	400/55-17.5	31x15.50-15	280/85 R20	340/65 R18
Min. ext. width (mm)	1380	1445	1460	1410	1420	1460	1690	1690	1415	1485
Ground clearance (mm)	286	298	286	320	275	330	282	242	341	300
Weight in order of speed (Kg):	TX with roll bar: 2070÷2170			with frame: 2120÷2220			with cab: 2210÷2310			
	TRX with roll bar: 2080÷2180			with frame: 2130÷2230			with cab: 2220÷2320			
Standard Features	<ul style="list-style-type: none"> • Reversible control tower (for TRX) • Rear or front/rear differential lock with electrohydraulic control • Lift arms fix type • Adjustable, suspension seat with safety belt • Protection roll bar • Adjustable wheel rims • Auxiliary rear hydraulic remotes with 1 double acting distributor with floating position, 1 oil reflow (total 3 quick couplings) • Rear adjustable height tow hitch • Front tow hitch • Multifunctional digital instrument • Battery • Electrical power point • Safety starting device on the inverter and PTO 									
Optional Features	<ul style="list-style-type: none"> • Star Light cab with air conditioning system and window on the roof, suspended on Silent Blocks • EasyStar safety frame with 6 uprights, fitted on Silent-block, with roof and left rear view mirror, (optional) front and rear windscreens complete with wipers and right rear view mirror • Lift and hydraulic quick couplers controlled by double speed "ON/OFF" Joystick (for TRX) • Rear power lift with suspension (for TRX) • Front power lift (for TRX) • Hydraulic power lift with draft and position control • Hydraulic third hitch and vertical tie-rod (for TRX) • Adjustable lifting arms with quick release couplings • Slider tow hitch • Pair of front/rear ballasts • Cast iron wheel flanges for 20" rear wheels • 6 front ballast weights • Front bullbar • Front lamp guards 									

The description and illustrations in this brochure are provided simply for information purposes; they are not binding and may be varied at any time without notice.

ANTONIO CARRARO SPA
Via Caltana, 24
35011 Campodarsego Padova ITALY
info@antoniocarraro.it
antoniocarraro.com

COD. 4 7318 142 - 06/2012