



# Motor-mower FC 206 - FC 206 E



**WHEEL AXLE**  
Wheel track adjustable in various positions. With protection caps.



**FAST COUPLING**  
The built-in fast coupling allows replacement of various implements with maximum ease.



**SICKLE BAR IN OIL BATH**  
Detail of the finger bar with compensator movement in oil bath.



MODEL FC 206								
Engine	Gearbox	PTO	Clutch	Handlebars	Wheel axle	Safety device	Sickle bar	Weight
Petrol and diesel 4 to 6.6 Kw (4.6-9 HP)	4-speed 2 forward+ 2 reverse gear	Independent 1 speed	Dry multi- disc	Adjustable in height	Rigid wheels 16x6.50-8	Safety switch combined with clutch lever	Movement in oil bath, 110 cm finger cutter bar with fast coupling	85 Kg
MODEL FC 206 E								
Engine	Gearbox	PTO	Clutch	Handlebars	Wheel axle	Safety device	Sickle bar	Weight
Petrol and diesel 4 to 6.6 Kw (4.6-9 HP)	4 speeds 2 forward+ 2 reverse gear	Independent 1 speed	Dry multi- disc	Adjustable in height	Rigid wheels 4.00-8	Safety switch combined with clutch lever	Eccentric movement, 100 cm bar with fast coupling	75 Kg

Implements: snow thrower, rotary mower.