## **Two-wheel tractor Kombi 98**



PRECISE RATIOS
Slow forward gear for cultivating.
Faster reverse gear for mowing.



HANDLEBARS
Reversible, adjustable in height and side to side for front or rear mounted attachments.



**FAST COUPLING**Simplifies replacement of various implements.



DIESEL ENGINE



| MODEL KOMBI 98                                                                     |                                                        |                        |                     |                       |            |                                                         |                                               |        |
|------------------------------------------------------------------------------------|--------------------------------------------------------|------------------------|---------------------|-----------------------|------------|---------------------------------------------------------|-----------------------------------------------|--------|
| Engine                                                                             | Gearbox                                                | РТО                    | Clutch              | Reversible handlebars | Wheel axle | Safety<br>device                                        | Rotary<br>tiller                              | Weight |
| Petrol and<br>diesel<br>3.5 to 4.8 Kw<br>(4.6-6.5 HP)                              | 2-speed<br>1 forward+<br>1 reverse gear<br>in oil bath | Independent<br>1 speed | Conical in oil bath | ,                     |            | Safety switch<br>+ PTO disen-<br>gagement<br>in reverse | 50 cm<br>adjustable,<br>with fast<br>coupling | 85 Kg  |
| Implements: iron wheels, trailed furrower, sickle bar, rotary mower, snow thrower. |                                                        |                        |                     |                       |            |                                                         |                                               |        |